

MANIFOLD CABINET



Surface type cabinet for installing heating circuit distributors. Removable doors allow for easy and convenient installation of distributors. It is possible to mounted cabinet while laying the heating system or after all "dirty" works (screeds, painting, etc.).

Standard execution, monted in recess:

- body made of hot-dip galvanized sheet, front made of steel sheet lacquered with [Facade type polyester powder paint](#) for outside usage, UV resistant. The standard color is white (RAL 9003).
- full, removable door, without hinges
- height and depth adjustment
- version without bottom, on the back of the cabinet there are adjustable strips for mounting accessories
- "coin operated" lock



Standard execution, mounted on the wall:

- steel sheet lacquered with [Facade type polyester powder paint](#) for outside usage, UV resistant. The standard color is white (RAL 9003).
- full door, removable, without hinges
- performance without back and bottom
- height adjustment
- "coin operated" lock

Monted in recess				
Number of manifold sections	Height [mm]	Width [mm]	Width [mm]	Code

4	700-790	400	110-160	S-ROZDZ-4S-WBPD-S
6		480		S-ROZDZ-6S-WBPD-S
8		610		S-ROZDZ-8S-WBPD-S
10		760		S-ROZDZ-10S-WBPD-S
12		840		S-ROZDZ-12S-WBPD-S
14		1100		S-ROZDZ-14S-WBPD-S
16		1200		S-ROZDZ-16S-WBPD-S
Monted on the wall				
4	700	400	130	S-ROZDZ-4S-ZBPD-S
6		480		S-ROZDZ-6S-ZBPD-S
8		610		S-ROZDZ-8S-ZBPD-S
10		760		S-ROZDZ-10S-ZBPD-S
12		840		S-ROZDZ-12S-ZBPD-S
14		1100		S-ROZDZ-14S-ZBPD-S
16		1200		S-ROZDZ-16S-ZBPD-S


POSSIBILITY OF IMPLEMENTATION



INOX

Stainless steel type 304 with 240 cut or 316L. In aggressive environment (e.g. swimming pools) recommended is only 316L steel

TYPE OF LOCK





PATENT LOCK - WITHOUT A KEY

PPUH SUPRON 3 Sp. z o.o.
Poland
26-600 Radom, Sadownicza 6

phone: (48) 48 363 89 98
(48) 48 363 99 65
e-mail: export@supron.pl

VAT EU: PL9482224948

SWIFT INGBPLPW

IBAN PL 17 1050 1793 1000 0024 0216 9680

We created for Your safety!