


INTERNAL HYDRANT DN33 MOUNTED IN RECESS WITH PLACE FOR FIRE EXTINGUISHER AND MCP-SIDE VERSION



| Product symbol | Product code |
|--|--------------|
| PN-EN 671-1[TW-33/20G]ROP-side version | S-33R-WBG30 |
| PN-EN 671-1[TW-33/20G]ROP-side version | S-33R-WBG20 |

Internal hydrant DN33 mounted in recess with place for fire alarm Manual Call Point – dimensions of the hole according to the customer's specification, with 33 mm semi-rigid fire hose. Holes for water connection are blanked. Working pressure from 0,2 to 0,7 MPa.



Hydrant weight: about 46 kg



Industry pallet (120 x 100 x height up to 200 cm): 2 pcs.

HYDRANT DIMENSION:

Height: 1200 mm
Width: 400 mm
Depth: 800 mm

RECESS DIMENSION:

Height: 1220 mm
Width: 420 mm
Depth: 810 mm

SUPPORTING LEGS: (option)

Height: 450 mm
Amount: 2 pcs.



Hydrant protected by:

- trademark established by protective law no 185129
- EU industrial design no 001777418-0002

Standard design:

- hydrant cabinet GALVANIZED steel sheet lacquered with [Facade type polyester powder paint](#) in red (RAL 3000) or white (RAL 9003) color; thanks to cover hinge cabinet door are opening for 180°
- place for fire alarm Manual Call Point – dimensions of the hole according to the customer's specification
- 52 aluminum hydrant valve with slant reduction
- fire hose reel in RAL 3000 color, with water axis
- $\varnothing 33$ mm semi-rigid fire hose 20 m or 30 m length according to PN-EN 694, fixed connection to water axis by crimping the hose with aluminum sleeve
- hydrant nozzle type PWh-33 according to PN-EN-671-1, fixed connection to fire hose by crimping the nozzle with aluminum sleeve
- valve and water axis connection hose; all thread connections without hose clamps
- Patent lock
- 4-piece frame for self-assembly
- marking: sign "Hydrant" and "Fire Extinguisher" according to PN-EN ISO 7010:2012 + information plate according to PN-EN 671-1
- documentation: instruction of assembly and maintenance
- guarantee card
- identification number

HYDRAULIC PROPERTIES

Working pressure: from 0,2 MPa to 0,7 MPa

Diffused conical water stream – not less than 45 degree.

| | hydrant valve 52 mm | ball valve 32 mm |
|--|---------------------|------------------|
|--|---------------------|------------------|

| Flow rate /efficiency/ | Pressure [MPa] | Dispersed stream | Compact stream | Dispersed stream | Compact stream |
|--|----------------|------------------|----------------|------------------|----------------|
| Equivalent diameter 12 mm | 0,2 | 107 l/min | 90 l/min | 108 l/min | 91 l/min |
| | 0,4 | 151 l/min | 128 l/min | 152 l/min | 129 l/min |
| | 0,6 | 184 l/min | 157 l/min | 185 l/min | 158 l/min |
| Factor K | | 75 | 64 | 76 | 64 |
| Effective coverage range of the water stream (+ the length of the hose 20 or 30 m) | | | | | |
| Equivalent diameter 12 mm | 0,2 | 4,1 m | 10,4 m | 4,2 m | 10,6 m |

Attention! The dependence of the flow rate Q on the pressure P is given by the equation: $Q = K\sqrt{10P}$, where Q is expressed in liters / minute and P in megapascals.

POSSIBILITY OF IMPLEMENTATION



INOX

Stainless steel type 304 with 240 cut or 316L. In aggressive environment (e.g. swimming pools) recommended is only 316L steel



LASER-CUT PATTERN

On the door, using a laser cutter, we can cut any pattern, lettering or logo



SAFETY GLASS

Door with matt or transparent glass. Any graphic can be used



PLEXI WINDOW

Window in door protected by plexi



INDIVIDUAL COLOR

Any color from RAL pallet



NON-STANDARD DIMENSIONS

Possible to adopt dimensions to customer request



NOZZLE CRIMPING

- nozzle crimping with aluminum sleeve in standard
- nozzle crimping with brass sleeve



52 VALVE WITH SLANT REDUCTION


Hydrant can be connected to DN52 water supply due to 52 valve with slant reduction



BALL VALVE 32 – OPTIONAL

Possible to use 5/4" ball valve (32)

TYPE OF LOCK



PATENT LOCK

Large quantity of cabinets can be opened with one key. The key for emergency opening is located behind the safety glass.



EURO LOCK

Twist lock adapted to put seal on.