

FIRE FOAM UNIT 52




JP-52 fire foam unit is used for fire protection of the object with heavy or medium foam.

DIMENSIONS: Height: 1400 mm Width: 650 mm Depth: 400 mm

Fire foam unit with flat folding hose 52 allows to extinguish fires by means of:

- heavy foam using a foam nozzle
- medium foam using a foam generator
- medium or heavy foam using a foam generator or a foam nozzle
- in each case, with water (for example after using foam concentrate) after replacing the foam nozzle with a hydrant nozzle



The operating time (foaming) can be extended by using an external foam concentrate tank. Each foam unit can be adapted to the user's needs, for example to store additional fire-fighting equipment, fire hoses, etc.

Application:

- Fuel storage
- Magazines for paints and varnishes
- Fuel transshipment stations
- Boiler room /engine room
- Other places with a high degree of fire hazard

Standard execution:

- zinc galvanized steel sheet [lacquered with Facade type polyester powder paint](#). The solution is resistant to weather conditions and UV radiation. Full door. The standard color is red (RAL 3000)
- hydrant valve 52
- 52mm flat folded pressure fire hose placed in the basket
- linear sucker Z-2 or Z-4
- hose to the sucker with a diameter of 25 mm
- foam concentrate ROTEOR M 3% or AFFF 3% – 50 kg – additional equipment
- foam generator PP-2 or PP-4 for heavy foam, or

- foam generator WP-2 or WP-4 for medium foam
- Pwh-52 hydrant fire-hose nozzle in accordance with PN-EN-671-2

Maximum / Recommended supply pressure	1,6 / 0,9 MPa
Efficiency for PP-2	200l/min
Efficiency for WP-2	200l/min
Working time for foam concentrate 3%	~ 8 minutes

POSSIBILITY OF IMPLEMENTATION



INOX

Stainless steel type 304 with 240 cut or 316L. In aggressive environment (e.g. swimming pools) recommended is only 316L steel



PLEXI WINDOW

Window in door protected by plexi



INDIVIDUAL COLOR

Any color from RAL pallet



NON-STANDARD DIMENSIONS

Possible to adopt dimensions to customer request

TYPE OF LOCK



PATENT LOCK

Large quantity of cabinets can be opened with one key. The key for emergency opening is located behind the safety glass.



PATENT LOCK - WITHOUT A KEY



EURO LOCK

Twist lock adapted to put seal on.

Przedsiębiorstwo Produkcyjno Usługowo Handlowe SUPRON 3 Spółka z o.o.

SUPRON3
WWW.SUPRON.PL



Certyfikat jakości wg PN-EN ISO 9001:2015-10

PPUH SUPRON 3 Sp. z o.o.
Poland
26-600 Radom, Sadownicza 6

phone: (48) 48 363 89 98
(48) 48 363 99 65
e-mail: export@supron.pl

VAT EU: PL9482224948

SWIFT INGBPLPW

IBAN PL 17 1050 1793 1000 0024 0216 9680

We created for Your safety!