

## WG TYPE PRESSURE FIRE HOSES WITH RUBBER INSERT FOR PUMPS



Product symbol	Product code
WG-52-20-ŁA DUNLOP	S-WM52-20-G-A
WG-75-20-ŁA DUNLOP	S-WM75-20-G-A



WG type pressure fire hose for fire pumps and auto pumps with a rubber insert. Diameter  $\phi$  52 and 75 mm length 20 m.


WG type pressure fire hoses are produced from the highest quality hose tape with a DUNLOP rubber insert.

### Execution:

- hoses in accordance with national and European requirements
- round-woven from high-quality polyester yarn
- with DUNLOP insert – working temperature from  $-50^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$
- innovative technology of connecting the hose with the connector eliminating the hose wiping at the end of the connector sleeve, improving ergonomics and aesthetics – solution protected by the PPR law No. 62999



### The innovative technology of connecting the hose with the connector by bush overlapping ensures:



- 100% tightness on connecting the tape with the connector
  - resistance to hose wiping at the end of the connector sleeve
  - improving ergonomics and aesthetics
- The solution is protected by the UPPR (Polish Patent Office) law No. 62999*

Braid	round-woven from high-quality polyester yarn		
Inner insert	DUNLOP rubber insert		
Type of fire-hose	<b>WG-52-20-ŁA</b>		<b>WG-75-20-ŁA</b>
Inner diameter	52 mm		75 mm
Length		20 m	
Connectors	Made of aluminium		
Working pressure		1,5 MPa	
Bursting pressure	6,4 MPa		5,7 MPa

Working temperature	-50°C +80°C	
The weight of the hose with connectors	5,5 kg	8 kg

## POSSIBILITY OF IMPLEMENTATION



### HOSE COUPLING

- aluminum - standard
- brass