

SUCTION FIRE HOSES 110 PCV



Product symbol	Product code
B-110-2500-Ł	S-WS110-2,5-V-A
B-110-1600-Ł	S-WS110-1,6-V-A



110 suction fire hoses are designed for sucking water or water solutions of extinguishing agents with underpressure up to 0.085 MPa. Suction hoses are used as conduits between the tank and the water pump. We make suction hoses with diameters of 25, 50, 75, 110, 125 mm and length from 1 up to 30 running meters.


Execution:

- reinforced hoses made of PVC – green color
- The connector is riveted with an aluminum bush. The lack of hose bands guarantees tightness over the entire lifetime of the hose

Mark:

- CNBOP-PIB logo
- certificate number
- the manufacturer's name
- hose type

The innovative technology of connecting the hose with the connector by bush overlapping ensures:



- the lack of bands guarantees 100% tightness when connecting the tape with the connector
- resistance to hose wiping at the end of the connector sleeve
- improving ergonomics and aesthetics

Commercial code (length 2500 mm)	B-110-2500-Ł
Commercial code (length 1600 mm)	B-110-1600-Ł
Terminal	Connectors 110

Thickness of the wall	7,6 mm
Underpressure	to 0,085 MPa
Length "L"	2500 / 1600 mm
Working temperature	from -20°C to +60°C