

INTERNAL HYDRANT DN52 WITH ROTARY REEL AND PLACE FOR FIRE EXTINGUISHER – SIDE VERSION



Internal hydrant DN52 with $\phi 52$ mm lay-flat fire hose wound on a rotary reel with place for fire extinguisher – side version. Mounted on the wall (C) or recessed (B). Holes for water connection are blanked. Working pressure from 0,2 to 0,7 MPa.



Hydrant weight: about 31 kg



Euro pallet (120 x 80 x height up to 200 cm): 6 pcs.

HYDRANT DIMENSION:

Height: 900 mm
Width: 250 mm
Depth: 700 mm


RECESS DIMENSION:

Height: 920 mm
Width: 270 mm
Depth: 710 mm



Standard design:

- hydrant cabinet STANDARD – steel sheet lacquered with [Facade type polyester powder paint](#) in red (RAL 3000) or white (RAL 9003) color; thanks to cover hinge cabinet door are opening for 180°
- hydrant in a suspended (C) or recessed (B) version. Recessed version supplied with flange
- 52 hydrant valve
- hose support – rotating reel in RAL 3000 color
- lay flat hose $\phi 52$ mm 15 m or 20 m length according to PN-EN 14540:2005(U)
- hydrant nozzle type PWh-52 according to PN-EN-671-2, fixed connection to fire hose by crimping the nozzle with aluminum sleeve
- hose couplings crimped with aluminum sleeve
- Patent lock
- marking: sign “Hydrant” and “Fire Extinguisher” according to PN-EN ISO 7010:2012 + information plate according to PN-EN 671-2
- documentation: instruction of assembly and maintenance, guarantee card
- identification number



Code	Type	Hose length	Lock	Supports/bases * [height x depth]	Number of supports/bases	Technical drawing	Instruction
------	------	-------------	------	--------------------------------------	--------------------------	-------------------	-------------

S-52-C1BG620-P-XXXX	mounted on the wall	20 m	Patent	S-C-PODSTAWA-550×250	2 pcs.		
S-52-C1BG615-P-XXXX	mounted on the wall	15 m					
S-52-B1BG620-P-XXXX	mounted in a recess	20 m					
S-52-B1BG615-P-XXXX	mounted in a recess	15 m					

XXXX – means a color from the RAL palette (red 3000 or white 9003)
 * Bases or supports are additional equipment sold separately

HYDRAULIC PROPERTIES

Working pressure: from 0,2 MPa to 0,7 MPa

Diffused conical water stream – not less than 45 degree.

Flow rate /efficiency/	Pressure [MPa]	Dispersed stream	Compact stream
Equivalent diameter 13 mm	0,2	172 l/min	155 l/min
	0,4	244 l/min	220 l/min
	0,6	299 l/min	270 l/min
Factor K	–	122	110
Effective range of the water jet projection (plus the length of the hose 15 m or 20 m)			
Equivalent diameter 13 mm	0,2	5,4 m	10,8 m
	0,4	8,1 m	17,1 m
	0,6	9,9 m	19,8 m

Attention! The dependence of the flow rate Q on the pressure P is given by the equation: $Q = K\sqrt{10P}$, where Q is expressed in liters / minute and P in megapascals.

POSSIBILITY OF IMPLEMENTATION



GALVANIZED STEEL SHEET

Lacquered with **Facade** type polyester facade paint. Solution resistant to atmospheric condition and UV radiation




INOX

Stainless steel type 304 with 240 cut or 316L. In aggressive environment (e.g. swimming pools) recommended is only 316L steel



LASER-CUT PATTERN

On the door, using a laser cutter, we can cut any pattern, lettering or logo



SAFETY GLASS

Door with matt or transparent glass. Any graphic can be used



PLEXI WINDOW

Window in door protected by plexi



INDIVIDUAL COLOR

Any color from RAL pallet



NON-STANDARD DIMENSIONS

Possible to adopt dimensions to customer request



NOZZLE CRIMPING

- nozzle crimping with aluminum sleeve in standard
- nozzle crimping with brass sleeve



NOZZLE CONNECTION WITH HOSE

- nozzle crimping with sleeve
- nozzle connected with adapter



52 HYDRANT VALVE

- 52 aluminum valve in standard
- 52 brass valve with aluminum adapter



BASES / SUPPORTS

TYPE OF LOCK



PATENT LOCK

Large quantity of cabinets can be opened with one key. The key for emergency opening is located behind the safety glass.



EURO LOCK

Twist lock adapted to put seal on.